WE'RE NOT JUST CREATING REMOTE CONTROLS, WE'RE CREATING A SAFER WORKPLACE

NOVA C

COMPACT AND STURDY WITH UNQUESTIONABLE SAFETY THAT IS BUILD TO LAST

The NOVA C impresses with its sturdy but attractive design. No compromises are made in regard to functionality and operator friendliness. Like most Hetronic products, the NOVA C transmitter is designed to fit a broad variety of applications, it's ideal for loader cranes, overhead cranes, concrete pumps and other mobile equipment.



Convince yourself of the high quality and ergonomics of the Nova C operator control unit. More information is available from your nearest Hetronic dealer.



HOUSING	Impact ResistantPolymer Composite	FREQUENCY RANGE	• 2.405-2.485GHz (FHSS)
DIMENSIONS	 H: 143mm x W: 242mm x D: 164mm H: 5.62" x W: 9.52" x D: 6.45" 	ANTENNA	Internal (* external on request)
WEIGHT	Max. 2.2Kg (2.3 lbs.); depends on configuration	STANDARD POWER RF OUTPUT EIRP (50 OHM)	Sub 1GHz: 25mW max or subject to country legislation 2.4GHz: 100mW
ENVIRONMENTAL PROTECTION	Min IP 65 (Exceeds Nema 12/13)	OPERATING TIME	• >30hrs of continuous operation on single charge
DPERATING TEMPERATURE/ STORAGE TEMPERATURE	 -20C to +70C (-4F to +158F) -40C to +85C (-40F to +185F) 	SAFETY	Enhanced Rolling Code, AES-128 or AES-256 encryption Active and Passive STOP function Parity and Checksum Minimum CAT3 PLd STOP and user controls
BATTERY RATING/TYPE	2x 3.7V Li-ion rechargeable UN38.3 IEC62133 certified battery pack	RESPONSE TIME	Less than 70ms
BATTERY CHARGER	Dependent on battery type (Included with TX and battery)	OPERATING RANGE	Typical line of sight > 250m. Varies depending RF output.
DIAGNOSTICS	Status LED for operation and standard/advanced low battery detection	OPTIONS	 Neck Belt Palm sensor with LED Signal Battery Hot Swapping Tilt sensor Footpath LED lighting Sunlight readable TFT Color Display
HUMIDITY RANGE	• 0 to 97% max. non-condsensing	TYPICAL CONTROL CONFIGURATION OPTIONS	One (1) or Two (2) axis spring return to center stepped Up to six (6) single axis proportional paddle levers Any combination of key switches, toggle switches, push buttons, rotary switches and stop switch Mushroom type "PUSH" STOP Switch Maintained off/on/program transmitt Power key switch with removable ke cap Momentary start/horn push

ABOUT HETRONIC

hetronic.com

Since 1982 Hetronic has delivered the finest, most reliable industrial Safety Radio Remote Control user interface solutions for process and equipment control applications in the industry.

We have shipped over 500,000 safe and reliable transmitter/ receiver solutions to customers around the world. Our global network of service locations, in over 50 countries, provides expert service, support and sales when customers need safe, secure and reliable remote control solutions. Contact a Hetronic expert and learn more at www.hetronic.com





